


1.7 x 8.75 MiniModule® PRODUCT DATA SHEET





Note: All dimensions are nominal values.

Contactor Characteristics	
	1.7 x 8.75
Cartridge Configuration	Parallel Flow. Lumenside Liquid Flow.
Liquid Side Flow Guidelines	<2500 ml/min (0.66 gpm)
Membrane	X50 Fiber
Porosity	40% Porosity
OD / ID	300µm OD/220µm ID
Potting Material	Polyurethane
Active Surface Area	ID: 1.0m ² (10.7 ft ²) OD: 1.4m ² (15.0 ft ²)
Number of Fibers	7400
Maximum Temperature/Pressure	4.2 kg/cm ² (4.1 bar, 60 psig) at 25°C (77°F) 3.2 kg/cm ² (3.1 bar, 45 psig) at 45°C (113°F)
Priming Volume (ID)	Lumenside 73 ml Shellside 132 ml
Housing Characteristics	
Material	Polycarbonate
Flange Connections	
Shellside (Gas / Vacuum)	Standard Female Luer Lock <i>Supplied with two 1/8 inch Hosebarb adaptors which mate to 1/4 inch ID tubing</i>
Lumenside (Wetted Surface)	1/4 inch FNPT
Seal Options	
Material	Applications
EPDM (ANSI / NSF61, FDA CFR Title Compliant)	General Purpose
Weight (with adapters)	
Dry	0.22 kg (0.48 lbs.)
Liquid Full (Lumenside)	0.29 kg (0.64 lbs.)
Shipping Weight	0.40 kg (0.88 lbs.)

All components of the MiniModule® Membrane Contactor, when used in accordance with recommendations given in our product literature for treatment or processing of water, non-alcoholic beverages, and aqueous, acid and non-acid food products at and below ambient temperatures, are in compliance with all relevant FDA regulations as specified in Title 21 of the Code of Federal Regulations.

1.75 x 8.75 MiniModule® PRODUCT DATA SHEET



Curves represent nominal values, generated using deionized water on the Lumenside at 20°C.

DO removal curves generated with vacuum drawn on both Shellside ports.

Characteristics may change under different operating conditions.

This product is to be used only by persons familiar with its use. It must be maintained within the stated limitations. All sales are subject to Seller's terms and conditions. Purchaser assumes all responsibility for the suitability and fitness for use as well as for the protection of the environment and for health and safety involving this product. Seller reserves the right to modify this document without prior notice. Check with your representative to verify the latest update. To the best of our knowledge, the information contained herein is accurate. However, neither Seller nor any of its affiliates assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Determination of the suitability of any material and infringement of any third party rights, including patent, trademark, or copyright rights, are the sole responsibility of the user. Users of any substance should satisfy themselves by independent investigation that the material can be used safely. We may have described certain hazards, but we cannot guarantee that these are the only hazards that exist. Nothing herein shall be construed as a recommendation or license to use any information that conflicts with any patent, trademark or copyright of Seller or others. Please read our Operating Manuals carefully before installing and using these modules.

THE INFORMATION CONTAINED HEREIN AND SELLER'S PRODUCTS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR USE, OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY. IN NO EVENT SHALL SELLER BE LIABLE FOR ANY SPECIAL, INCIDENTAL, INDIRECT, OR CONSEQUENTIAL DAMAGES OF ANY KIND, OR ANY DAMAGES WHATSOEVER RESULTING FROM THE USE OF INFORMATION CONTAINED HEREIN AND SELLER'S PRODUCTS.

Liqui-Cel®, SuperPhobic®, MiniModule®, and MicroModule® are registered trademarks of Membrana-Charlotte, A Division of Celgard, LLC.

Copyright © 2011 Membrana – Charlotte

All rights reserved. (D87 rev 2)

Membrana - Charlotte
A Division of Celgard, LLC
13800 South Lakes Drive
Charlotte, North Carolina 28273
USA
Phone: (704) 587 8888
Fax: (704) 587 8610

Membrana GmbH
Oehder Strasse 28
42289 Wuppertal
Germany
Phone: +49 202 6099 - 658
Phone: +49 6126 2260 - 41
Fax: +49 202 6099 - 750

Japan Office
Shinjuku Mitsui Building, 27F
1-1, Nishishinjuku 2-chome
Shinjuku-ku, Tokyo 163-0427
Japan
Phone: 81 3 5324 3361
Fax: 81 3 5324 3369

MEMBRANA
A POLYPORE COMPANY

www.liqui-cel.com

